

Calibrated Okoume

Choose the core, bond and emission specification

Okoume names the face veneer, not a single core or glue construction. The calibrated hardwood BWR option and the separately specified E1 eucalyptus option below must not be treated as interchangeable. The quotation identifies the selected construction and documentation.

Attribute	Specification
Face	Okoume (Aucoumea klaineana), pale and uniform
Hardwood BWR construction	Hardwood core, Okoume face, MUF (melamine-urea-formaldehyde) glue with a BWR (boiling-water-resistant) bond; 16 or 18 mm, subject to quotation
Separate E1 construction	Eucalyptus core for the calibrated E1 construction; E1 test report available on request for the lot quoted
Calibration	Sanded to a held thickness; final tolerance confirmed in the quote
E1 reference variant	16 mm E1 eucalyptus-core panel at approximately 32 kg per nominal 8 x 4 ft sheet; this weight is not a specification for every calibrated Okoume option
Finish	Bare for the buyer's finish or HPL-laminated where specified
Other builds	Okoume face is also available on MR IS 303 and BWR packing constructions
Supply	FOB Cochin export quotation; sheet size, face combination and quantity confirmed before production

Commercial note

This sheet contains no public price. Quantity, sheet size, destination, availability, final tolerance and delivery terms change the offer and are confirmed by the sales team in the written quotation. Email sales@cochinwood.in or use the quote form at cochinwood.in/contact.