

Film-Faced Shuttering Plywood

MUF/BWR and PF/BWP choices for concrete formwork

Select the bond, thickness and nominal sheet weight for slab decks, columns or wall forms. The options below are an enquiry guide, not a stock guarantee. The written quotation confirms availability, batch weight and the final construction.

Attribute	Specification
Water-resistant bond	MUF (melamine-urea-formaldehyde glue), BWR (boiling-water-resistant) bond
Waterproof bond	PF (phenol-formaldehyde glue), BWP (boiling-waterproof) bond
MUF / BWR options	10 mm: 21, 22 kg; 11 mm: 24 kg; 12 mm: 26, 28, 30, 34 kg; 18 mm: 35, 40, 45, 50 kg
PF / BWP options	12 mm: 30, 34 kg; 18 mm: 35, 40, 45, 50 kg
38 kg enquiry	18 mm, 38 kg: bond grade confirmed before quotation; do not assume BWR or BWP from weight alone
Manufactured sheet	8 x 4 ft (2440 x 1220 mm) only; all listed weights are nominal per sheet
Core / film	Hardwood core; film on both faces. Film weight, colour and edge sealing confirmed for the selected construction
Standard / tests	The applicable standard and bond grade are stated on the quote; test certificates available on request for the lot quoted
Re-use	Depends on handling, cleaning, support spacing and edge care; no fixed pour count applies to every grade
Supply	Full truckload ex-works Perumbavoor within India; 20 ft or 40 ft container FOB Cochin for export. Part-loads within India and LCL for export are available where the route and quantity allow; the practical minimum is confirmed on the quotation

Commercial note

This sheet contains no public price. Quantity, sheet size, destination, availability, final tolerance and delivery terms change the offer and are confirmed by the sales team in the written quotation. Email sales@cochinwood.in or use the quote form at cochinwood.in/contact.