

Commercial Plywood (Packing Grade)

Standard rubberwood-core MR panel; BWR bond on written request

Commercial plywood and packing-grade plywood are names for the same family in our range. The standard construction is a rubberwood-core MR panel for packing and suitable general work. The written quotation confirms the face, bond, finished thickness, tolerance and intended use.

Attribute	Specification
Trade names	Commercial plywood / packing-grade plywood
Standard core	Rubberwood; any alternative core and permitted defects must be agreed on the quote
Standard bond	MR (moisture-resistant); IS 303 where specified on the quote. The standard MR panel is not waterproof or for permanent wet service
On-request bond	BWR (boiling-water-resistant) for suitable humid service, only when the written quote confirms the grade and construction; not a marine specification
Face options	Confirm the supplied face; Okoume or Gurjan available on request
Thickness	Standard range 6-18 mm; occasional larger sizes against order. The quote confirms the exact finished thickness and minus tolerance
Standard sheet	8 x 4 ft (2440 x 1220 mm); other sizes cut to order
Typical use	Cases, crates, pallets and suitable general-purpose work. Furniture use requires the quoted face, finish, bond and tolerance to suit the job
Supply	Full truckload ex-works Perumbavoor within India; FOB Cochin for export. Part-loads within India and LCL for export are available where the route and quantity allow; the practical minimum is confirmed on the quotation

Commercial note

This sheet contains no public price. Quantity, sheet size, destination, availability, final tolerance and delivery terms change the offer and are confirmed by the sales team in the written quotation. Email sales@cochinwood.in or use the quote form at cochinwood.in/contact.